



## MOUNTED MECHANICAL SEED DRILL

Agrional Mounted Mechanical Seed Drill is a mounted type sowing machine which can precisely and properly sow every kind of grain seeds (wheat, barley, rye, rapeseed, oats, peas, soybeans, alfalfa) on the row. In addition, it can successfully sow small vegetable seeds such as spinach and parsley. Sowing units can be produced with double discs or Axe type. There are models with fertilizer and without fertilizer. This is a seeder which can sow on ridge and flat land. Seeds are delivered in desired amount by adjusting with gearbox.

It has adjustable sowing rate, 2 - 450 kg/ha.  
 It's easy adjustable, strong and useful machine.  
 It can sow on all kinds of land; ridge and flat land.  
 Sowing units are designed to apply the same pressure on ground surface at any height, thus, it obtains uniform planting pattern.  
 As all seeds fall into the same depth, it ensures simultaneous germination.  
 It can sow at minimum 12,5 cm distance between rows.  
 Sowing units can be mounted or demounted when required.  
 Precision and easy sowing norm can be adjusted, thanks to changeable gearbox. Gearbox runs quietly.

Rear covers are with spring.  
 Hydraulic marker system is available.  
 It's a machine with high work efficiency.  
 It can be produced with fertilizer or without fertilizer.  
 Sowing units can be Axe type or double disc type according to demand.  
 You can adjust desired seed amount per decare, thanks to sowing test before sowing. According to demand, all marking can be adjusted with row marker. Press adjustments of sowing units can be done separately.

Model	Working Width	Coulter Quantity	Distance Between Rows	Seed Tank Volume	Average Weight With Fertilizer	Width	Length	Height From Tank	Height From Marker	Tire Dimensions	Required Power
	mm	pcs	cm	lt	kg	mm	mm	mm	mm		hp
AGM-HMY 21	2520	21	120	473	820	2060	2550	1410	2150	500x15	60
AGM-HMY 25	3000	25	120	590	960	2060	3050	1410	2400	500x15	70
AGM-HMY 29	3480	29	120	707	1120	2060	3600	1450	2400	600x16	80
AGM-HMY 33	3960	33	120	825	1205	2060	4100	1450	2650	600x16	90