



MOUNTED REVERSIBLE MOULDBOARD PLOUGH

Time savings and reduced fuel consumption. Ease and speed of set-up into the work/transport position. Ease and simple adjustments for the best tractor adaptations. Box section top quality steel frame construction.

Model	Number of Furrows	Clearance	Distance Between Furrows	Working Width	Working Depth	Weight	Required Power
		cm	cm	cm	cm	kg	Hp
AG-RMP 12-2	2	75	80	25-30-35	26	700	55-60
AG-RMP 12-3	3	75	80	25-30-35	26	840	60-70
AG-RMP 12-4	4	75	80	25-30-35	26	1115	80-90
AG-RMP 12-5	5	75	80	25-30-35	26	1320	90-110
AG-RMP 14-2	2	75	80	30-35-40	28	704	60-65
AG-RMP 14-3	3	75	80	30-35-40	28	911	65-70
AG-RMP 14-4	4	75	80	30-35-40	28	1145	85-90
AG-RMP 14-5	5	75	80	30-35-40	28	1400	90-110
AG-RMP 16-2	2	75	85	35-40-45	30	710	80-85
AG-RMP 16-3	3	75	85	35-40-45	30	918	80-85
AG-RMP 16-4	4	75	85	35-40-45	30	1170	85-90
AG-RMP 16-5	5	75	85	35-40-45	30	1420	100-120
AG-RMP 18-2	2	75	85	40-45-50	32	716	80-90
AG-RMP 18-3	3	75	85	40-45-50	32	925	80-90
AG-RMP 18-4	4	75	85	40-45-50	32	1185	90-110
AG-RMP 18-5	5	75	85	40-45-50	32	1500	120-130

We reserve the right to make changes and or improvements in designs & dimensions without notice and without incurring obligation.