



ROTARY TILLER FIXED TYPE

Agrional fixed rotary tiller is a secondary tillage tool used in preparing seed beds, stubble ploughing in especially farms, vineyards and gardens. It is also a multi-purposed and long lasting environment friendly machine that helps with the increase of the humus content of the soil by incorporating the plant residues and organic fertilizer into the soil and it does not make it a necessity to fight with the chemical weeds.

Model	Working Width	Working Depth	Width	Length	Height	Number of Flange	Number of Horizontal Blades	Weight	Required Power
	mm	mm	mm	mm	mm	pcs	pcs	kg	hp
AG-RT 140	1260	190	1516	850	1100	6	30	390	30-35
AG-RT 160	1514	190	1770	850	1100	7	36	420	35-40
AG-RT 185	1768	190	2024	850	1100	8	42	455	40-45
AG-RT 210	2022	190	2278	850	1100	9	48	490	45-50
AG-RT 240	2240	190	2570	900	1230	10	54	760	55-65
AG-RT 250	2495	190	2825	900	1230	11	60	850	70-75
AG-RT 160 Variable Spin	1514	190	1790	850	1200	7	36	575	50-55
AG-RT 185 Variable Spin	1768	190	2044	850	1200	8	42	600	55-60
AG-RT 210 Variable Spin	2022	190	2298	850	1200	9	48	665	60-65
AG-RT 240 Variable Spin	2240	190	2590	900	1230	10	54	785	70-75
AG-RT 250 Variable Spin	2495	190	2825	900	1230	11	60	880	75-80

We reserve the right to make changes and or improvements in designs & dimensions without notice and without incurring obligation.