



## MOUNTED FIELD SPRAYER STANDARD BOOM

- The chassis models are produced with high quality material by robotic welding.
- The lock system with pressure spring support the booms opening and closing stably .there is control panel that provides homogeneous and precise spraying.
- Cleanable filter system, 3 membrane spraying pump with best performance,
- Fresh water tank independent from main tank.
- Long lasting and cleanable nozzle, the tank washing system, which enables the tank to be washed after sprayin.

Model		DELTA A4	DELTA A6	DELTA A8	DELTA A10
Material of Tank		Polyethylene	Polyethylene	Polyethylene	Polyethylene
Capacity of Tank	Lt	400	600	800	1000
Pump Model		C71	C71	C71	C71
Pump Flow	l/min	71	71	71	71
Pump Pressure	Bar	50	50	50	50
Control Panel		OG 403	OG 403	OG 403	OG 403
Work Width	m	10	10	10	10
Nozzle Type		Conical brass nozzle			
Number of Nozzles		20	20	20	20
Distance Between Nozzles	cm	50	50	50	50
Boom Height Adjustment		Manual	Manual	Manual	Manual
Boom's Folding Adjustment		Manual	Manual	Manual	Manual
Required Tractor Power	HP	40	40	40	40
Operating Speed	r/min	540	540	540	540
Weight	kg	145	156	202	210
Length	cm	135	135	148	148
Width	cm	75	75	75	75
Height	cm	135	150	156	176

We reserve the right to make changes and or improvements in designs & dimensions without notice and without incurring obligation.