



TRAILED ATOMIZER

- Draining system that quickly drains the water remaining in the tank after spraying
- Fast filling
- Control that provides homogeneous and precise spraying norm
- Spraying pump with 4 membranes having the best performance
- Filter system with check valve that can be cleaned easily
- Durable wheels that can operate in all kinds of field conditions
- Pressure filter that increases spraying efficiency by filtering pressurized water
- Stop lamps that ensure safety of the machine in traffic
- Atomizer nozzle with adjustable spray angle and drop stopping feature
- Fan protection wire designed to prevent possible accidents
- Drawbar that has height adjustment and can be attached to the tractor easily

Model		FICUS P 1000	FICUS P 1600	FICUS P 2000
Material Of Tank		Polyester	Polyester	Polyester
Capacity of Tank	lt	1000	1600	2000
Pump Model		C 145	C 145	C 145
Pump Flow	lt/min	145	145	145
Pump Pressure	Bar	50	50	50
Control Panel		OTR 17	OTR 17	OTR 17
Nozzle Type		Brass Sopper Turbo	Brass Stopper Turbo	Brass Stopper Turbo
Number of Nozzle	Pcs	16	16	16
Fan Diameter	cm	85	90	90
Working Width	cm	20-24	20-24	20-24
Required Tractor Power	BG	70	70	70
Operating Speed	R/min	540	540	540
Air Flow Rate	m ³ /h	66000	66000	66000
Weight	kg	516	550	550
Width	cm	168	178	180
Length	cm	365	365	410
Height	cm	135	135	135

We reserve the right to make changes and or improvements in designs & dimensions without notice and without incurring obligation.